

# Flanged Miniature Bearings -- Inch



Inch (Decimal)			Open Bearing			Shielded Bearing (ZZ)			Sealed Bearing (2RS)		
Bore <b>d</b>	OD <b>D</b>	Flange OD <b>Df</b>	Width <b>B</b>	Flange Width <b>Bf</b>	Reference	Width <b>B</b>	Flange Width <b>Bf</b>	Reference	Width <b>B</b>	Flange Width <b>Bf</b>	Reference
0.0400	0.1250	0.1710	0.0469	0.0130	FR09						
0.0469	0.1562	0.2030	0.0625	0.0130	FR0	0.0937	0.0310	FR0ZZ			
0.0550	0.1875	0.2340	0.0781	0.0230	FR1	0.1094	0.0310	FR1ZZ			
0.0781	0.2500	0.2960	0.0937	0.0230	FR1-4	0.1406	0.0310	FR1-4ZZ			
0.0937	0.1875	0.2340	0.0625	0.0180	FR133	0.0937	0.0310	FR133ZZ			
0.0937	0.3125	0.3590	0.1094	0.0230	FR1-5	0.1406	0.0310	FR1-5ZZ			
0.1250	0.2500	0.2960	0.0937	0.0230	FR144	0.1094	0.0310	FR144ZZ			
0.1250	0.3125	0.3590	0.1094	0.0230	FR2-5	0.1406	0.0310	FR2-5ZZ	0.1406	0.0310	FR2-5-TTS
0.1250	0.3750	0.4220	0.1094	0.0230	FR2-6	0.1406	0.0310	FR2-6ZZ	0.1406	0.0310	FR2-6-TTS
0.1250	0.3750	0.4400	0.1562	0.0300	FR2	0.1562	0.0300	FR2ZZ	0.1562	0.0300	FR2-2RS
0.1562	0.3125	0.3590	0.1094	0.0230	FR155	0.1250	0.0360	FR155ZZ			
0.1875	0.3125	0.3590	0.1094	0.0230	FR156	0.1250	0.0360	FR156ZZ	0.1250	0.0360	FR156-TTS
0.1875	0.3750	0.4220	0.1250	0.0230	FR166	0.1250	0.0310	FR166ZZ	0.1250	0.0310	FR166-TTS
0.1875	0.5000	0.5650	0.1562	0.0420	FR3	0.1960	0.0420	FR3ZZ	0.1960	0.0420	FR3-2RS
0.1875	0.5000	0.5650	0.1960	0.0420	FR3W19						
0.2500	0.3750	0.4220	0.1250	0.0230	FR168	0.1250	0.0350	FR168ZZ	0.1250		
0.2500	0.5000	0.5470	0.1250	0.0230	FR188	0.1875	0.0450	FR188ZZ	0.1875	0.0450	FR188-TTS
0.2500	0.6250	0.6900	0.1960	0.0420	FR4	0.1960	0.0420	FR4ZZ	0.1960	0.0420	FR4-2RS
0.3125	0.5000	0.5470	0.1562	0.0310	FR1810	0.1562	0.0310	FR1810ZZ			
0.3750	0.8750	0.9690	0.2188	0.0620	FR6	0.2812	0.0620	FR6ZZ	0.2812	0.0620	FR6-2RS
0.5000	1.1250	1.2252	0.2500	0.0620	FR8	0.3125	0.0620	FR8ZZ	0.3125	0.0620	FR8-2RS
0.6250	1.3750	1.5000	0.2812	0.0687	FR10	0.3438	0.0687	FR10ZZ	0.3438	0.0687	FR8-2RS