



NMB Inch Miniature Bearings



Bore d"	OD D"	Width B"	Radial Ref	Flanged Ref	Flange Dia Df"	Flange Width Bf"	Standard Ref
0.0400	0.1250	0.0469	DDRI-2	DDRIF-2	0.013	0.171	R0-9
0.0469	0.1562	0.0625	DDRI-21/2	DDRIF-21/2	0.013	0.203	R0
0.0469	0.1562	0.0937	DDRI-21/2-Z	DDRIF-21/2-Z	0.013	0.203	R0
0.0469	0.1562	0.0937	DDRI-21/2-ZZ	DDRIF-21/2-ZZ	0.013	0.203	R0
0.0550	0.1875	0.0781	DDRI-3	DDRIF-3	0.023	0.234	R1
0.0550	0.1875	0.0937	DDRI-3-Z	—	—	—	R1
0.0550	0.1875	0.1094	—	DDRIF-3-Z	0.023	0.234	R1
0.0550	0.1875	0.1094	DDRI-3-ZZ	DDRIF-3-ZZ	0.023	0.234	R1
0.0781	0.2500	0.0937	DDRI-4	DDRIF-4	0.023	0.296	R1-4
0.0781	0.2500	0.1094	DDRI-4-Z	—	—	—	R1-4
0.0781	0.2500	0.1406	—	DDRIF-4-Z	0.023	0.296	R1-4
0.0781	0.2500	0.1406	DDRI-4-ZZ	DDRIF-4-ZZ	0.023	0.296	R1-4
0.0937	0.1875	0.0625	DDRI-3332	DDRIF-3332	0.018	0.234	R133
0.0937	0.1875	0.0937	DDRI-3332-Z	DDRIF-3332-Z	0.018	0.234	R133
0.0937	0.1875	0.0937	DDRI-3332-ZZ	DDRIF-3332-ZZ	0.018	0.234	R133
0.0937	0.3125	0.1094	DDRI-5	DDRIF-5	0.023	0.359	R1-5
0.0937	0.3125	0.1094	DDRI-5-Z	—	—	—	R1-5
0.0937	0.3125	0.1406	—	DDRIF-5-Z	0.023	0.359	R1-5
0.0937	0.3125	0.1406	DDRI-5-ZZ	DDRIF-5-ZZ	0.023	0.359	R1-5
0.1250	0.2500	0.0937	DDRI-418	DDRIF-418	0.023	0.296	R144
0.1250	0.2500	0.0937	DDRI-418-Z	—	—	—	R144
0.1250	0.2500	0.1094	—	DDRIF-418-Z	0.023	0.296	R144
0.1250	0.2500	0.1094	—	DDRIF-418-ZZ	0.023	0.296	R144
0.1250	0.3125	0.1094	DDRI-518	DDRIF-518	0.023	0.359	R2-5
0.1250	0.3125	0.1094	DDRI-518-Z	—	—	—	R2-5
0.1250	0.3125	0.1406	—	DDRIF-518-Z	0.023	0.359	R2-5
0.1250	0.3125	0.1406	DDRI-518-ZZ	DDRIF-518-ZZ	0.023	0.359	R2-5
0.1250	0.3750	0.1094	DDRI-618	DDRIF-618	0.023	0.422	R2-6
0.1250	0.3750	0.1094	DDRI-618-Z	—	—	—	R2-6
0.1250	0.3750	0.1406	—	DDRIF-618-Z	0.023	0.422	R2-6
0.1250	0.3750	0.1406	DDRI-618-ZZ	DDRIF-618-ZZ	0.023	0.422	R2-6
0.1250	0.3750	0.1562	DDR-2	DDRF-2	0.030	0.440	R-2
0.1250	0.3750	0.1562	DDR-2-Z	DDRF-2-Z	0.030	0.440	R-2
0.1250	0.3750	0.1562	DDR-2-ZZ	DDRF-2-ZZ	0.030	0.440	R-2



* Basic references shown include code "DD" for NMB developed 400 series Martensitic stainless steel. If chrome steel is desired, delete "DD".

NMB Inch Miniature Bearings



Bore d"	OD D"	Width B"	Radial Ref	Flanged Ref	Flange Dia Df"	Flange Width Bf"	Standard Ref
0.1562	0.3125	0.1094	DDRI-5532	DDRIF-5532	0.023	0.359	R155
0.1562	0.3125	0.1094	DDRI-5532-Z	—	—	—	R155
0.1562	0.3125	0.1250	—	DDRIF-5532-Z	0.023	0.359	R155
0.1562	0.3125	0.1250	DDRI-5532-ZZ	DDRIF-5532-ZZ	0.023	0.359	R155
0.1875	0.3125	0.1094	DDRI-5632	DDRIF-5632	0.023	0.359	R156
0.1875	0.3125	0.1094	DDRI-5632-Z	—	—	—	R156
0.1875	0.3125	0.1250	—	DDRIF-5632-Z	0.023	0.359	R156
0.1875	0.3125	0.1250	DDRI-5632-ZZ	DDRIF-5632-ZZ	0.023	0.359	R156
0.1875	0.3750	0.1250	DDRI-6632	DDRIF-6632	0.023	0.422	R166
0.1875	0.3750	0.1250	DDRI-6632-Z	DDRIF-6632-Z	0.023	0.422	R166
0.1875	0.3750	0.1250	DDRI-6632-ZZ	DDRIF-6632-ZZ	0.023	0.422	R166
0.1875	0.5000	0.1562	DDR-3	DDRF-3	0.042	0.565	R-3
0.1875	0.5000	0.1960	DDR-3-Z	DDRF-3-Z	0.042	0.565	R-3
0.1875	0.5000	0.1960	DDR-3-ZZ	DDRF-3-ZZ	0.042	0.565	R-3
0.2500	0.3750	0.1250	DDRI-614	DDRIF-614	0.023	0.422	R168
0.2500	0.3750	0.1250	DDRI-614-Z	DDRIF-614-Z	0.023	0.422	R168
0.2500	0.3750	0.1250	DDRI-614-ZZ	DDRIF-614-ZZ	0.023	0.422	R168
0.2500	0.5000	0.1250	DDRI-814	DDRIF-814	0.023	0.547	R188
0.2500	0.5000	0.1250	DDRI-814-Z	—	—	—	R188
0.2500	0.5000	0.1875	—	DDRIF-814-Z	0.023	0.547	R188
0.2500	0.5000	0.1875	DDRI-814-ZZ	DDRIF-814-ZZ	0.023	0.547	R188
0.2500	0.6250	0.1960	DDR-4	DDRF-4	0.042	0.690	R-4
0.2500	0.6250	0.1960	DDR-4-Z	DDRF-4-Z	0.042	0.690	R-4
0.2500	0.6250	0.1960	DDR-4-ZZ	DDRF-4-ZZ	0.042	0.690	R-4
0.2500	0.7500	0.2188	DDRI-1214	—	—	—	R-4A
0.2500	0.7500	0.2812	DDRI-1214-Z	—	—	—	R-4A
0.2500	0.7500	0.2812	DDRI-1214-ZZ	—	—	—	R-4A
0.3125	0.5000	0.1562	DDRI-8516	DDRIF-8516	0.031	0.547	R1810
0.3125	0.5000	0.1562	DDRI-8516-Z	DDRIF-8516-Z	0.031	0.547	R1810
0.3125	0.5000	0.1562	DDRI-8516-ZZ	DDRIF-8516-ZZ	0.031	0.547	R1810
0.3750	0.6250	0.1562	DDRI-1038	—	—	—	R620
0.3750	0.6250	0.1562	DDRI-1038-Z	—	—	—	R620
0.3750	0.6250	0.1562	DDRI-1038-ZZ	—	—	—	R620
0.3750	0.8750	0.2188	DDRI-1438	—	—	—	R-6

* Bearings with metal shields have "Z" or "ZZ" at the end of the reference.

NMB Inch Miniature Bearings



Bore d"	OD D"	Width B"	Radial Ref	Flanged Ref	Flange Dia Df"	Flange Width Bf"	Standard Ref
0.3750	0.8750	0.2812	—	DDRIF-1438	0.062	0.969	
0.3750	0.8750	0.2812	DDRI-1438-Z	DDRIF-1438-Z	0.062	0.969	R-6
0.3750	0.8750	0.2812	DDRI-1438-ZZ	DDRIF-1438-ZZ	0.062	0.969	R-6
0.5000	0.7500	0.1562	DDRI-1212	—	—	—	R824
0.5000	0.7500	0.1562	DDRI-1212-Z	—	—	—	R824
0.5000	0.7500	0.1562	DDRI-1212-ZZ	—	—	—	R824
0.6250	0.8750	0.1562	DDRI-1458	—	—	—	R1028
0.6250	0.8750	0.1562	DDRI-1458-Z	—	—	—	R1028
0.6250	0.8750	0.1562	DDRI-1458-ZZ	—	—	—	R1028
0.7500	1.0000	0.1562	DDRI-1634	—	—	—	R1232
0.7500	1.0000	0.1562	DDRI-1634-Z	—	—	—	R1232
0.7500	1.0000	0.1562	DDRI-1634-ZZ	—	—	—	R1232